

# Panel Series



## *LED PANEL LIGHTS SELECTION*



### SPECIFICATION

Model	GH-B8020-606	GH-B8020-412	GH-B8020-406
Dimensions	597x597x80mm	1197x397x80mm	597x397x80mm
Luminous flux	3700lm		2000lm
Mounting	Recessed / Suspended		
Class	Class I		Class I
IP rating	IP20		IP20
Power consumption	37W		20W
Power factor	>0.9		>0.9
lm/W	100lm/W		100lm/W
CRI	>80		>80
CCT	3000K / 4000K / 6500K		3000K / 4000K / 6500K
Lifetime (hrs)	50,000		
Operating Temperature	0°C-35°C		0°C-35°C



### STANDARDS

- IEC/EN60598-1,
- IEC/EN60598-2-1,
- IEC/EN60598-2-2.



### SPECIFICATION

Model	GH-B8021-312
Dimensions	1200x300x100mm
Luminous flux	4400lm
Mounting	Suspended
Class	Class I
IP rating	IP20
Power consumption	55W
Power factor	>0.9
lm/W	80lm/W
CRI	>80
CCT	3000K / 4000K / 6500K
Lifetime (hrs)	50,000
Operating Temperature	0°C-35°C



### STANDARDS

- IEC/EN60598-1,
- IEC/EN60598-2-1,
- IEC/EN60598-2-2.



### SPECIFICATION

Model	GH-B8022-606	GH-B8022-312	GH-B8022-612
Dimensions	595x595x35mm	1195x295x35mm	595x295x35mm
Luminous flux	3700-4000lm		5000-5500lm
Mounting	Recessed / Suspended		
Class	Class II		Class II
IP rating	IP20		IP20
Power consumption	36W		50W
Power factor	>0.9		>0.9
lm/W	100-110lm/W		100-110lm/W
CRI	>80		>80
CCT	3000K / 4000K / 6500K		3000K / 4000K / 6500K
Lifetime (hrs)	50,000		
Operating Temperature	0°C-35°C		0°C-35°C



### STANDARDS

- IEC/EN60598-1,
- IEC/EN60598-2-1,
- IEC/EN60598-2-2.



### SPECIFICATION

Model	GH-B8023-606	GH-B8023-312	GH-B8023-612
Dimensions	595x595x9mm	1195x295x9mm	1195x595x9mm
Luminous flux	3700-4000lm		5000-5500lm
Mounting	Recessed / Suspended		
Class	Class II		Class II
IP rating	IP20		IP20
Power consumption	36W		50W
Power factor	>0.9		>0.9
lm/W	100-110lm/W		100-110lm/W
CRI	>80		>80
CCT	4000K		4000K
Lifetime (hrs)	50,000		
Operating Temperature	0°C-35°C		0°C-35°C



### STANDARDS

- IEC/EN60598-1,
- IEC/EN60598-2-1,
- IEC/EN60598-2-2.

# Panel-03

## LED PANEL LIGHT SELECTION



### SPECIFICATION

Model	GH-B8024-606	GH-B8024-312	GH-B8024-306
Dimensions	597x597x80mm	1197x297x80mm	597x297x80mm
Luminous flux	3700-4000lm		5000-5500lm
Mounting	Recessed / Suspended		
Class	Class I		Class I
IP rating	IP20		IP20
Power consumption	37W		50W
Power factor	>0.9		>0.9
lm/W	100-110lm/W		100-110lm/W
CRI	>80		>80
CCT	3000K / 4000K / 6500K		3000K / 4000K / 6500K
Lifetime (hrs)	50,000		
Operating Temperature	0°C-35°C		0°C-35°C




### STANDARDS

- IEC/EN60598-1,
- IEC/EN60598-2-1,
- IEC/EN60598-2-2.



### SPECIFICATION

Model	GH-B8025-406	GH-B8025-412
Dimensions	615x415x75mm	1215x415x75mm
Luminous flux	1100lm	2500lm
Mounting	Recessed / Suspended	
Class	Class I	
IP rating	IP20	
Power consumption	14W	28W
Power factor	>0.9	>0.9
lm/W	80lm/W	90lm/W
CRI	>80	>80
CCT	3000K / 4000K / 6500K	
Lifetime (hrs)	50,000	
Operating Temperature	0°C-35°C	




### STANDARDS

- IEC/EN60598-1,
- IEC/EN60598-2-1,
- IEC/EN60598-2-2.



### SPECIFICATION

Model	GH-B8026-606	GH-B8026-312	GH-B8026-412
Dimensions	597x597x80mm	1197x297x80mm	1197x397x80mm
Luminous flux	3700-4070lm	3700-4070lm	5500-6050lm
Mounting	Recessed / Suspended		
Class	Class I	Class I	Class I
IP rating	IP20	IP20	IP20
Power consumption	37W	37W	55W
Power factor	>0.9	>0.9	>0.9
lm/W	100-110lm/W	100-110lm/W	100-110lm/W
CRI	>80	>80	>80
CCT	3000K / 4000K	3000K / 4000K	3000K / 4000K
Lifetime (hrs)	50,000		
Operating Temperature	0°C-35°C	0°C-35°C	0°C-35°C



### STANDARDS

- IEC/EN60598-1,
- IEC/EN60598-2-1,
- IEC/EN60598-2-2.



### SPECIFICATION

Model	GH-B8027-606	GH-B8027-312
Dimensions	597x597x80mm	1197x297x80mm
Luminous flux	3700-4070lm	3700-4070lm
Mounting	Recessed / Suspended	
Class	Class I	Class I
IP rating	IP20	IP20
Power consumption	37W	37W
Power factor	>0.9	>0.9
lm/W	100-110lm/W	100-110lm/W
CRI	>80	>80
CCT	3000K / 4000K	3000K / 4000K
Lifetime (hrs)	50,000	
Operating Temperature	0°C-35°C	0°C-35°C



### STANDARDS

- IEC/EN60598-1,
- IEC/EN60598-2-1,
- IEC/EN60598-2-2.



### SPECIFICATION

Model	GH-B8029-406	GH-B8029-412
Dimensions	597x397x80mm	1197x397x80mm
Luminous flux	2000-2200lm	3700-4070lm
Mounting	Recessed / Suspended	
Class	Class I	Class I
IP rating	IP20	IP20
Power consumption	20W	37W
Power factor	>0.9	>0.9
lm/W	100-110lm/W	100-110lm/W
CRI	>80	>80
CCT	3000K / 4000K / 6500K	3000K / 4000K / 6500K
Lifetime (hrs)	50,000	
Operating Temperature	0°C-35°C	0°C-35°C



### STANDARDS

- IEC/EN60598-1,
- IEC/EN60598-2-1,
- IEC/EN60598-2-2.



### SPECIFICATION

Model	GH-B8030-412	GH-B8030-612
Dimensions	1198x398x80mm	1194x584x80mm
Luminous flux	3700-4070lm	3700-4070lm
Mounting	Recessed / Suspended	
Class	Class I	Class I
IP rating	IP20	IP20
Power consumption	37W	37W
Power factor	>0.9	>0.9
lm/W	100-110lm/W	100-110lm/W
CRI	>80	>80
CCT	3000K / 4000K / 6500K	3000K / 4000K / 6500K
Lifetime (hrs)	50,000	
Operating Temperature	0°C-35°C	0°C-35°C



### STANDARDS

- IEC/EN60598-1,
- IEC/EN60598-2-1,
- IEC/EN60598-2-2.

# Panel-06

## LED PANEL LIGHT SELECTION



### SPECIFICATION

Model	GH-B8031-315
Dimensions	1485x298x80mm
Luminous flux	3700-4000lm
Mounting	Recessed / Suspended
Class	Class I
IP rating	IP20
Power consumption	37W
Power factor	>0.9
lm/W	100-110lm/W
CRI	>80
CCT	3000K / 4000K / 6500K
Lifetime (hrs)	50,000
Operating Temperature	0°C-35°C



### STANDARDS

- IEC/EN60598-1,
- IEC/EN60598-2-1,
- IEC/EN60598-2-2.



### SPECIFICATION

Model	GH-B8032-312
Dimensions	1500x300x70mm
Luminous flux	3700-4000lm
Mounting	Recessed / Suspended
Class	Class I
IP rating	IP20
Power consumption	37W
Power factor	>0.9
lm/W	100-110lm/W
CRI	>80
CCT	3000K / 4000K / 6500K
Lifetime (hrs)	50,000
Operating Temperature	0°C-35°C



### STANDARDS

- IEC/EN60598-1,
- IEC/EN60598-2-1,
- IEC/EN60598-2-2.


# Panel-07

## LED PANEL LIGHT SELECTION



### SPECIFICATION

Model	GH-B8033-312
Dimensions	1244x297x83mm
Base Type	T8
Mounting	Recessed / Suspended
Class	Class I
IP rating	IP20
Power consumption	2x36W (LED T8)
Power factor	100-110mW
lm/W	>0.9
CRI	/
CCT	3000K / 4000K / 6500K
Lifetime (hrs)	50,000
Operating Temperature	0°C-35°C



### STANDARDS

- IEC/EN60598-1,
- IEC/EN60598-2-1,
- IEC/EN60598-2-2.



### SPECIFICATION

Model	GH-B8037-312
Dimensions	1200x265x55mm
Luminous flux	3850-4400lm
Mounting	Suspended
Class	Class I
IP rating	IP20
Power consumption	55W
Power factor	>0.9
lm/W	70-80lm/W
CRI	>80
CCT	3000K / 4000K / 6500K
Lifetime (hrs)	50,000
Operating Temperature	0°C-35°C



### STANDARDS

- IEC/EN60598-1,
- IEC/EN60598-2-1,
- IEC/EN60598-2-2.

# Panel-08

## LED PANEL LIGHT SELECTION



### SPECIFICATION

Model	GH-B8035-606	GH-B8035-312	GH-B8036-612
Dimensions	597x597x55mm	1197x297x55mm	1197x597x55mm
Luminous flux	4000-4400lm		6000-6600lm
Mounting	Recessed / Suspended		
Class	Class I		Class I
IP rating	IP20		IP20
Power consumption	40W		60W
Power factor	>0.9		>0.9
lm/W	100-110lm/W		100-110lm/W
CRI	>80		>80
CCT	3000K / 4000K / 6500K		3000K / 4000K / 6500K
Lifetime (hrs)	50,000		
Operating Temperature	0°C-35°C		0°C-35°C



### STANDARDS

- IEC/EN60598-1,
- IEC/EN60598-2-1,
- IEC/EN60598-2-2.



### SPECIFICATION

Model	GH-B8036-606	GH-B8036-312	GH-B8036-612
Dimensions	597x597x80mm	1197x297x80mm	1197x597x80mm
Luminous flux	4000-4400lm		6000-6600lm
Mounting	Recessed / Suspended		
Class	Class I		Class I
IP rating	IP54		IP54
Power consumption	40W		60W
Power factor	>0.9		>0.9
lm/W	100-110lm/W		100-110lm/W
CRI	>80		>80
CCT	3000K / 4000K / 6500K		3000K / 4000K / 6500K
Lifetime (hrs)	50,000		
Operating Temperature	0°C-35°C		0°C-35°C



### STANDARDS

- IEC/EN60598-1,
- IEC/EN60598-2-1,
- IEC/EN60598-2-2.